



**GAS COMPONENTS**



**ELECTRIC COMPONENTS**



**WATER TECHNOLOGY**



**MECHANICAL COMPONENTS**



**TOOLS**

Spare parts suitable for

**ANFIM**

Find the complete and up-to-date range of products in our GEV Webshop



# Manufacturer catalogue

The most important spare parts and accessories arranged clearly for every manufacturer

- ✓ Complete product range and all appliance data always up to date in the GEV Webshop
- ✓ Alphabetical Index at the end of the catalogue

## GEV Webshop

[www.gev-online.co.uk](http://www.gev-online.co.uk)

[www.gev-online.com](http://www.gev-online.com)



- 🔍 Add to Favourites
- 🔍 Sign In with email address and usual password
- 🔍 Easy-order – place several items in your basket at the same time
- 🔍 Quick Item search – no login needed




## switches and momentary switches

### rocker/momentary rocker switches

30x22mm



1


<b>GEV No.</b>	301002	<b>Ref. No.</b>	89
<b>description</b>	rocker switch mounting measurements 30x22mm orange 2NO 250V 16A illuminated 0-I connection male faston 6.3mm ambient temperature max. 85/125°C protection IP65		
<b>accessories for</b>	301002		
	<b>GEV No.</b>	301036	<b>Ref. No.</b>
			—
	protective cover internal size 30x22mm for rocker switch mounting measurementsmm		

### microswitches

universal




1

<b>GEV No.</b>	345042	<b>Ref. No.</b>	4-A
<b>description</b>	microswitch with plunger 250V 16A 1CO connection male faston 6.3mm L 28mm ambient temperature max. 125°C mounting distance 22mm type EF83161.3 actuating force: 75g blue/black		
<b>accessories for</b>	345042		
	<b>GEV No.</b>	345043	<b>Ref. No.</b>
			—
	lever set 5-piece		

pin-plunger actuated



1

<b>GEV No.</b>	345042	<b>Ref. No.</b>	4-A
<b>description</b>	microswitch with plunger 250V 16A 1CO connection male faston 6.3mm L 28mm ambient temperature max. 125°C mounting distance 22mm type EF83161.3 actuating force: 75g blue/black		
<b>accessories for</b>	345042		
	<b>GEV No.</b>	345043	<b>Ref. No.</b>
			—
	lever set 5-piece		

with push button

gas ignition



1

<b>GEV No.</b>	347250	<b>Ref. No.</b>	260
<b>description</b>	microswitch with push button 250V 12A 1NO connection male faston 6.3mm L1 29mm ambient temperature max. 125°C mounting distance 22mm type VRSR03AA1 actuating force: 200g thread M10x0.75		
<b>For models:</b>	Haus-Self		

## lamps

### indicator lights

indicator lights (complete)

ø10mm

with screw socket



1

<b>GEV No.</b>	359482	<b>Ref. No.</b>	79
<b>description</b>	indicator light ø 10mm 400V green connection cable cable length 250mm temp.-resist. 90°C socket screw base		

## timers

### mechanical timers



1

<b>GEV No.</b>	360466 <sup>1</sup>	<b>Ref. No.</b>	88 88-C Z88
<b>description</b>	timer MT49 2-pole operation time 220s impulse mechanical 2NO at 250V 16A permanent position no shaft ø 6x4.6mm shaft 6x4.6mm shaft L 18mm mounting distance 28mm mounting thread M4 connection male faston 6.3mm ambient temperature max. 125°C with knob		

<sup>1</sup>incl. knob



## contactors

## ALLEN BRADLEY

## power contactors



1

<b>GEV No.</b>	380902	<b>Ref. No.</b>	91-A OLD
<b>description</b>	power contactor resistive load 20A 400VAC (AC3/400V) 2.5kW main contacts 3NO auxiliary contacts 1NO connection screw connection		

## OMRON

## power contactors



1

<b>GEV No.</b>	380883	<b>Ref. No.</b>	91-A
<b>description</b>	power contactor resistive load 20A 400VAC (AC3/400V) 4kW main contacts 3NO auxiliary contacts 1NO connection screw connection type J7KNA-09-10 OMRON		

## condensators &amp; interference suppression filters

## operating capacitors

## plastic



1

<b>GEV No.</b>	365118	<b>Ref. No.</b>	90-30
<b>description</b>	operating capacitor capacity 14/16μF 400V plastic-coated tolerance 5% 2-piece		
<b>For models:</b>	Caimano-Drogheria, Drogheria-Coffee-Shop		



1

<b>GEV No.</b>	365020	<b>Ref. No.</b>	90-14
<b>description</b>	operating capacitor capacity 14μF 400V tolerance 5%Hz ambient temperature max. -25 to +85°C ø 35mm L 70mm M8 plastic connection male faston 6.3mm protection		
<b>For models:</b>	Caimano, Lusso		



1

<b>GEV No.</b>	365121	<b>Ref. No.</b>	90-16
<b>description</b>	operating capacitor capacity 16μF 400V tolerance 5% 50/60Hz ambient temperature max. -40 up to +85°C ø 40mm L 72mm plastic connection male faston 6.3mm MLR25PRL protection		
<b>For models:</b>	Caimano-Special450-Timer, Super-Caimano, Super-Lusso		



1

<b>GEV No.</b>	365021	<b>Ref. No.</b>	88/16
<b>description</b>	operating capacitor capacity 16μF 425V tolerance 5% 50/60Hz ambient temperature max. -25 to +85°C ø 35mm L 73mm single M8 plastic connection male faston 6.3mm 416.10.99 protection		
<b>For models:</b>	Special450-Timer		



1

<b>GEV No.</b>	365120	<b>Ref. No.</b>	90-6
<b>description</b>	operating capacitor capacity 6μF 425V tolerance 5% 50/60Hz ambient temperature max. -25 to +85°C ø 30mm L 58mm plastic connection male faston 2.8mm 45M.B2E.6 protection		



1

<b>GEV No.</b>	365013	<b>Ref. No.</b>	90-8
<b>description</b>	operating capacitor capacity 8μF 400V tolerance 5%Hz ambient temperature max. -25 to +85°C ø 31.5mm L 55mm M8 plastic connection male faston 6.3mm protection		




## equipment-specific units

### for coffee grinders

#### grinding burrs

#### grinding burrs straight

#### standard



1

<b>GEV No.</b>	526216	<b>Ref. No.</b>	50
<b>description</b>	grinding burrs pair turn direction left D1 ø 50mm ID ø 30mm H 7.5mm tooth spacing 3mm hole ø 4.6mm bore ø 7.6mm mounting ø 38		



1

<b>GEV No.</b>	527210	<b>Ref. No.</b>	54
<b>description</b>	grinding burrs pair turn direction left D1 ø 54mm ID ø 32mm H 8mm tooth spacing 3.5mm hole ø 4.5mm bore ø 6.5mm mounting ø 42 straight suitable for ANFIM		



1

<b>GEV No.</b>	526217	<b>Ref. No.</b>	64
<b>description</b>	grinding burrs pair turn direction left D1 ø 64mm ID ø 37mm H 9mm tooth spacing 3.5mm hole ø 6mm bore ø 8mm mounting ø 46 straight suitable for ANFIM		



1

<b>GEV No.</b>	526218	<b>Ref. No.</b>	75-SP
<b>description</b>	grinding burrs pair turn direction left D1 ø 75mm ID ø 43.5mm H 9.2mm tooth spacing 3.5mm hole ø 6.5mm bore ø 10mm mounting ø 57		
<b>For models:</b>	Caimano-Drogheria, Special450-Automatico		



1


<b>GEV No.</b>	527211	<b>Ref. No.</b>	75
<b>description</b>	grinding burrs pair turn direction left D1 ø 75mm ID ø 43mm H 9mm tooth spacing 4mm hole ø 6.5mm bore ø 10.5mm mounting ø 57 straight suitable for ANFIM		

#### grinding burrs holders



1

<b>GEV No.</b>	526219	<b>Ref. No.</b>	53
<b>description</b>	grinding burr holder aluminium mounting pos. upper suitable for ANFIM		




1

<b>GEV No.</b>	526220	<b>Ref. No.</b>	55
<b>description</b>	grinding burr holder brass mounting pos. upper suitable for ANFIM		



1

<b>GEV No.</b>	526222	<b>Ref. No.</b>	250
<b>description</b>	grinding burr holder D1 ø 50mm aluminium mounting pos. upper suitable for ANFIM		
<b>For models:</b>	Haus-Self		





1


<b>GEV No.</b>	526215	<b>Ref. No.</b>	251
<b>description</b>	grinding burr holder D1 ø 50mm mounting pos. lower		
<b>For models:</b>	Haus-Self		




			
1			
<b>GEV No.</b>	526221	<b>Ref. No.</b>	220
<b>description</b>	grinding burr holder D1 ø 54mm aluminium mounting pos. upper suitable for ANFIM		
<b>For models:</b>	Best, Super-Best		


			
1			
<b>GEV No.</b>	526214	<b>Ref. No.</b>	229
<b>description</b>	grinding burr holder D1 ø 54mm mounting pos. lower		
<b>For models:</b>	Best, Super-Best		


			
1			
<b>GEV No.</b>	526212	<b>Ref. No.</b>	63
<b>description</b>	grinding burr holder D1 ø 64mm mounting pos. lower		

			
1			
<b>GEV No.</b>	526213	<b>Ref. No.</b>	66
<b>description</b>	grinding burr holder D1 ø 75mm mounting pos. lower		

## screws


			
1			
<b>GEV No.</b>	560393	<b>Ref. No.</b>	VS-54
<b>description</b>	flat-headed bolt thread M4 thread L 8.5mm brass Qty 1 pcs intake Phillips head ø 6mm head thickness 2.5mm		
<b>For models:</b>	Best, Super-Best		

			
1			
<b>GEV No.</b>	560394	<b>Ref. No.</b>	VS-64
<b>description</b>	flat-headed bolt thread M5 thread L 10mm Qty 1 pcs intake slotted head ø 7mm head thickness 3mm		
<b>For models:</b>	Caimano, Lusso		

			
1			
<b>GEV No.</b>	560067	<b>Ref. No.</b>	75VS VS-75
<b>description</b>	flat-headed bolt thread M5 thread L 10mm SS DIN 7985/ISO 7045 Qty 20 pcs intake Phillips head ø 8mm head thickness 2mm		
<b>For models:</b>	Caimano-Drogheria, Caimano-Special450-Automatico, Caimano-Special450-Timer, Drogheria-Coffee-Shop, Special450-Automatico, Special450-Timer, Super-Caimano, Super-Lusso		

## spillage trays

			
1			
<b>GEV No.</b>	526252	<b>Ref. No.</b>	238
<b>description</b>	drain tray L 165mm W 130mm suitable for ANFIM		
<b>For models:</b>	Best, Haus-Self, Super-Best		

			
1			
<b>GEV No.</b>	526253	<b>Ref. No.</b>	84
<b>description</b>	drain tray L 212mm W 155mm		

## dosing containers

## dosing container lids

			
1			
<b>GEV No.</b>	526247	<b>Ref. No.</b>	201
<b>description</b>	lid for dosing container ø 115.5mm		
<b>For models:</b>	Best		


			
1			
<b>GEV No.</b>	526245	<b>Ref. No.</b>	5
<b>description</b>	lid for dosing container ø 120.5mm		





			
1			
<b>GEV No.</b>	526246	<b>Ref. No.</b>	5-SPT
<b>description</b>	lid for dosing container ø 121.5mm		


			
1			
<b>GEV No.</b>	526244	<b>Ref. No.</b>	1-A
<b>description</b>	lid for dosing container ø 123.5mm with symbol arrow		


			
1			
<b>GEV No.</b>	526248	<b>Ref. No.</b>	216
<b>description</b>	lid for dosing container ø 125mm		
<b>For models:</b>	Best, Haus-Self		


<p>springs</p> <p>group 1</p>			
			
1			
<b>GEV No.</b>	526240	<b>Ref. No.</b>	231
<b>description</b>	holding pin wire gauge ø 2mm total length 101mm		
<b>For models:</b>	Best, Super-Best		


			
1			
<b>GEV No.</b>	526239	<b>Ref. No.</b>	213
<b>description</b>	spring wire gauge ø 1.6mm total length 51mm		
<b>For models:</b>	Best		


<p>glass cylinders</p>			
			
1			
<b>GEV No.</b>	526205	<b>Ref. No.</b>	202
<b>description</b>	cylinder for dosing container ø 110.5mm H 102mm		
<b>For models:</b>	Best		


			
1			
<b>GEV No.</b>	526182	<b>Ref. No.</b>	6-A
<b>description</b>	cylinder for dosing container ø 117mm H 113.5mm		

			
1			
<b>GEV No.</b>	526183	<b>Ref. No.</b>	6
<b>description</b>	cylinder for dosing container ø 130mm H 104mm		

			
1			
<b>GEV No.</b>	526189	<b>Ref. No.</b>	243
<b>description</b>	cylinder ø 130mm H 67mm		
<b>For models:</b>	Super-Best		

<p>levers</p> <p>bolts</p>			
			
1			
<b>GEV No.</b>	526197	<b>Ref. No.</b>	32
<b>description</b>	bolt for dosing pump D1 ø 4mm L 10mm		

<p>levers</p>			
			
1			
<b>GEV No.</b>	526231	<b>Ref. No.</b>	214
<b>description</b>	lever for dosing pump hole ø 25.5mm L 80mm		
<b>For models:</b>	Best		

			
1			
<b>GEV No.</b>	526230	<b>Ref. No.</b>	33
<b>description</b>	lever for dosing pump hole ø 30mm L 95mm		


## stoppers

			
1			
<b>GEV No.</b>	526201	<b>Ref. No.</b>	34
<b>description</b>	stopper for lever L 14mm W 10mm H 4mm mounting ø 6mm rubber		


## coffee presses


## components


## bolts

			
1			
<b>GEV No.</b>	526199	<b>Ref. No.</b>	22
<b>description</b>	bolt D1 ø 8mm D2 ø 12mm L 135mm T1: M8 T2: M8		


## holders


			
1			
<b>GEV No.</b>	526224	<b>Ref. No.</b>	24
<b>description</b>	bracket for coffee press L 39mm telescope		


			
1			
<b>GEV No.</b>	526223	<b>Ref. No.</b>	18
<b>description</b>	bracket for coffee press L 40mm thread M8x1.25 aluminium		

			
1			
<b>GEV No.</b>	526238	<b>Ref. No.</b>	215
<b>description</b>	bracket for coffee press ø 16mm L 46mm thread M8		
<b>For models:</b>	Best		

## pressers


			
1			
<b>GEV No.</b>	526211	<b>Ref. No.</b>	21
<b>description</b>	coffee press ø 45mm H 20.5mm thread M8 plastic		

			
1			
<b>GEV No.</b>	526210	<b>Ref. No.</b>	19-P
<b>description</b>	coffee press ø 52mm H 24mm thread M8 plastic		

			
1			
<b>GEV No.</b>	526209	<b>Ref. No.</b>	19-56 19-G
<b>description</b>	coffee press ø 56mm H 21mm thread M8 plastic		

## automatic grinding

## automatic grinding


			
1			
<b>GEV No.</b>	526236	<b>Ref. No.</b>	3-A
<b>description</b>	ring for dosing pump ø 128mm		


## sector plates


			
1			
<b>GEV No.</b>	526234	<b>Ref. No.</b>	25
<b>description</b>	sector plates plastic suitable for ANFIM		


			
1			
<b>GEV No.</b>	526235	<b>Ref. No.</b>	212
<b>description</b>	sector plates plastic suitable for ANFIM		
<b>For models:</b>	Best		





ratches			
ratches			
			
1			
<b>GEV No.</b>	526202	<b>Ref. No.</b>	210
<b>description</b>	ratchet for dosing pump $\varnothing$ 25mm internal size 7.5x10mm H 10.1mm brass		
<b>For models:</b>	Best		


			
1			
<b>GEV No.</b>	526200	<b>Ref. No.</b>	29
<b>description</b>	ratchet for dosing unit $\varnothing$ 30mm int. $\varnothing$ 1 10.4mm internal size 9x9mm H 9.7mm		


stars			
complete			
			
1			
<b>GEV No.</b>	526208	<b>Ref. No.</b>	15
<b>description</b>	star for dosing unit complete $\varnothing$ 111mm		


			
1			
<b>GEV No.</b>	526207	<b>Ref. No.</b>	207
<b>description</b>	star for dosing unit complete $\varnothing$ 98mm shaft $\varnothing$ 15 shaft length 40mm		
<b>For models:</b>	Best		


accessories			
			
1			
<b>GEV No.</b>	526241	<b>Ref. No.</b>	26 500026
<b>description</b>	clamping bracket L 74mm for dosing container		


			
1			
<b>GEV No.</b>	526204	<b>Ref. No.</b>	208
<b>description</b>	shaft with hex bolster $\varnothing$ 10mm L 24mm thread M5 brass		
<b>For models:</b>	Best		

spindles			
			
1			
<b>GEV No.</b>	526242	<b>Ref. No.</b>	36
<b>description</b>	spindle for dosing unit shaft $\varnothing$ 16.5mm shaft length 12mm T1: M8 T2: M6		

adjustment mechanism			
lockable adjustment			
			
1			
<b>GEV No.</b>	526198	<b>Ref. No.</b>	58
<b>description</b>	pressure pin for setting ring shaft $\varnothing$ 8mm shaft length 55mm		

			
1			
<b>GEV No.</b>	526237	<b>Ref. No.</b>	225
<b>description</b>	push button for setting ring L 29mm W 13mm shaft $\varnothing$ 6mm shaft length 25mm		
<b>For models:</b>	Best, Haus-Self		

screw connections			
			
1			
<b>GEV No.</b>	526196	<b>Ref. No.</b>	60
<b>description</b>	thread bolt $\varnothing$ 8mm thread M4 L 36mm		

accessories			
stickers			
			
1			
<b>GEV No.</b>	526190	<b>Ref. No.</b>	56
<b>description</b>	sticker for setting ring L 483mm W 4mm		

handles			
			
1			
<b>GEV No.</b>	526233	<b>Ref. No.</b>	453
<b>description</b>	handle for setting ring		
<b>For models:</b>	Lusso, Special450-Automatico, Special450-Timer, Super-Lusso		

## coffee powder dispenser

## coffee powder dispenser



1

<b>GEV No.</b>	526225	<b>Ref. No.</b>	261
<b>description</b>	coffee discharge chute stainless steel suitable for ANFIM		
<b>For models:</b>	Haus-Self		

## coffee beans containers

## container lids



1

<b>GEV No.</b>	526249	<b>Ref. No.</b>	218
<b>description</b>	lid for coffee beans container $\varnothing$ 141.5mm		
<b>For models:</b>	Drogheria-Coffee-Shop, Super-Best		



1

<b>GEV No.</b>	526250	<b>Ref. No.</b>	41
<b>description</b>	lid for coffee beans container $\varnothing$ 195mm		

## coffee beans containers



1

<b>GEV No.</b>	526181	<b>Ref. No.</b>	450
<b>description</b>	coffee beans container L 175mm W 175mm H 180mm		
<b>For models:</b>	Lusso, Special450-Automatico, Special450-Timer, Super-Lusso		



1

<b>GEV No.</b>	526185	<b>Ref. No.</b>	217
<b>description</b>	coffee beans container $\varnothing$ 130mm H 100mm		
<b>For models:</b>	Best, Haus-Self		



1

<b>GEV No.</b>	526186	<b>Ref. No.</b>	496
<b>description</b>	coffee beans container $\varnothing$ 150mm H 190mm		
<b>For models:</b>	Drogheria-Coffee-Shop		



1

<b>GEV No.</b>	526187	<b>Ref. No.</b>	40
<b>description</b>	coffee beans container ø 193mm H 185mm		



1


<b>GEV No.</b>	526188	<b>Ref. No.</b>	40-DR
<b>description</b>	coffee beans container ø 194mm H 231mm		
<b>For models:</b>	Caimano-Drogheria		



1


<b>GEV No.</b>	526184	<b>Ref. No.</b>	219
<b>description</b>	coffee beans container ø 200mm H 147mm		
<b>For models:</b>	Super-Best		

support for filter holder




1

<b>GEV No.</b>	526232	<b>Ref. No.</b>	228
<b>description</b>	filter holder support for dosing pump L 53mm W 47mm		
<b>For models:</b>	Best		




1

<b>GEV No.</b>	526228	<b>Ref. No.</b>	241
<b>description</b>	filter holder support for dosing pump L 70mm W 55mm		
<b>For models:</b>	Super-Best		




1

<b>GEV No.</b>	526226	<b>Ref. No.</b>	80
<b>description</b>	filter holder support for dosing pump long L 181mm W 60mm		



1

<b>GEV No.</b>	526227	<b>Ref. No.</b>	81
<b>description</b>	filter holder support for dosing pump short L 143mm W 50mm		




1

<b>GEV No.</b>	526229	<b>Ref. No.</b>	263
<b>description</b>	filter holder support for coffee grinder L 47mm W 50mm		
<b>For models:</b>	Haus-Self		

counters

counters



1

<b>GEV No.</b>	526243	<b>Ref. No.</b>	16
<b>description</b>	counter for dosing unit		

## equipment feet and end caps

## screw-in feet



1

<b>GEV No.</b>	697820	<b>Ref. No.</b>	237
<b>description</b>	equipment foot ø 20mm H 12.5mm Qty 1 pcs bore ø 3.5mm		
<b>For models:</b>	Best, Haus-Self, Super-Best		

## equipment feet with stem



1

<b>GEV No.</b>	802045	<b>Ref. No.</b>	94
<b>description</b>	equipment foot ø 25mm H 10mm mounting ø 10mm overall height 20mm rubber Qty 1 pcs		

## springs

## compression springs



1

<b>GEV No.</b>	526191	<b>Ref. No.</b>	23
<b>description</b>	compression spring ø 10.5mm L 70.5mm wire gauge ø 1mm		



1

<b>GEV No.</b>	526193	<b>Ref. No.</b>	30
<b>description</b>	compression spring ø 4.7mm L 26mm wire gauge ø 0.4mm		



1

<b>GEV No.</b>	526203	<b>Ref. No.</b>	224
<b>description</b>	compression spring ø 5.6mm L 24mm wire gauge ø 0.55mm		
<b>For models:</b>	Best, Haus-Self, Super-Best		



1

<b>GEV No.</b>	526192	<b>Ref. No.</b>	59
<b>description</b>	compression spring ø 7.8mm L 20mm wire gauge ø 0.7mm		

## tension springs



1

<b>GEV No.</b>	526194	<b>Ref. No.</b>	35
<b>description</b>	tension spring ø 10.5mm total length 43mm wire gauge ø 1mm L 42.5mm		



1

<b>GEV No.</b>	526195	<b>Ref. No.</b>	17 17AR
<b>description</b>	tension spring ø 7.5mm total length 35mm wire gauge ø 0.65mm		

## fastening material

## screws

## countersunk screws



1

<b>GEV No.</b>	501370	<b>Ref. No.</b>	473
<b>description</b>	countersunk screw thread M6 L 50mm SS DIN 963/ISO 2009 Qty 1 pcs intake slotted head ø 11mm		
<b>For models:</b>	Lusso, Special450-Automatico, Special450-Timer, Super-Lusso		

## flat-headed bolts



1


<b>GEV No.</b>	560067	<b>Ref. No.</b>	75VS VS-75
<b>description</b>	flat-headed bolt thread M5 thread L 10mm SS DIN 7985/ISO 7045 Qty 20 pcs intake Phillips head ø 8mm head thickness 2mm		
<b>For models:</b>	Caimano-Drogheria, Caimano-Special450-Automatico, Caimano-Special450-Timer, Drogheria-Coffee-Shop, Special450-Automatico, Special450-Timer, Super-Caimano, Super-Lusso		





1

<b>GEV No.</b>	560650	<b>Ref. No.</b>	VS-50
<b>description</b>	flat-headed bolt thread M4 thread L 8mm DIN 84/ISO 1207 Qty 1 pcs intake slotted head ø 7mm head thickness 2.5mm chrome-plated steel		
<b>For models:</b>	Haus-Self		




			
1			
<b>GEV No.</b>	560393	<b>Ref. No.</b>	VS-54
<b>description</b>	flat-headed bolt thread M4 thread L 8.5mm brass Qty 1 pcs intake Phillips head ø 6mm head thickness 2.5mm		
<b>For models:</b>	Best, Super-Best		

			
1			
<b>GEV No.</b>	560394	<b>Ref. No.</b>	VS-64
<b>description</b>	flat-headed bolt thread M5 thread L 10mm Qty 1 pcs intake slotted head ø 7mm head thickness 3mm		
<b>For models:</b>	Caimano, Lusso		

grub screws			
DIN 914/ISO 4027			
			
1			
<b>GEV No.</b>	697410	<b>Ref. No.</b>	31
<b>description</b>	grub screw thread M5 L 6mm stainless steel DIN 914/ISO 4027 WS 2.5 with spike Qty 1 pcs		


## nuts

### cap nuts

			
1			
<b>GEV No.</b>	560392	<b>Ref. No.</b>	57
<b>description</b>	cap nuts thread M11x1.75 WS 17 brass Qty 1 pcs		

### hexagonal nuts

#### hexagonal nuts metric (without norm)

			
1			
<b>GEV No.</b>	501369	<b>Ref. No.</b>	221
<b>description</b>	hexagonal nut thread M11x1.75 H 6mm WS 17 brass Qty 1 pcs DIN/ISO DIN 934 / ISO 4032/8673		
<b>For models:</b>	Best, Super-Best		





**C**

cap nuts	13
condensators & interference suppression filters	4
contactors	4
countersunk screws	12

**F**

fastening material	12
flat-headed bolts	12

**G**

grub screws	13
-------------	----

**H**

hexagonal nuts	13
----------------	----

**I**

indicator lights	3
indicator lights (complete)	3

**L**

lamps	3
-------	---

**M**

mechanical timers	3
microswitches	3

**N**

nuts	13
------	----

**O**

operating capacitors	4
----------------------	---

**R**

rocker/momentary rocker switches	3
----------------------------------	---

**S**

screws	12
switches and momentary switches	3

**T**

timers	3
--------	---